



306Q POS Tablet

Rugged, Multi-functional for Point-of-Service/Sales Applications

The 306Q POS Tablet integrates a 6" capacitive touchscreen, Qualcomm octa-core processor and Android operating system in a compact and robust packages for point-of-service/sale applications, inventory management, and field applications. Emphasizing superior integration and handling, the 306Q offers embedded POS-centric peripherals including magnetic stripe reader, barcode scanner, and NFC/RFID reader to provide accurate data collection and service efficiency in the restaurant, on the sales floor, and in the casinos and resorts.





Features

- 6" LED-backlight screen with capacitive touch
- Qualcomm[®] octa-core processor
- Android operating system
- MIL-STD-810H rated, 4-feet drop protection
- · Hot-swappable battery pack

Major Options

- 8 MP Back Camera
- Magnetic Stripe Reader
- 2D Barcode Scanner (Reads 1D and 2D)
- NFC/RFID Reader
- · GPS Module
- · 4G LTE/AWS

Specifications

Major Options System CPU Qualcomm Octa-Core, 2.0GHz RAM Storage 64GB Flash **Operating System** Android 9.0 and 10 6" LED-Backlight Capacitive Touchscreen Display **Display Resolution** 720 x 1440 **Network Interface** WLAN Wi-Fi 802.11ac, 2.4/5 GHz Dual Band I/O Ports **USB Ports** 1 x latest USB/charging 1 Micro SD Card Slot SD Slot · Digital Pen **Control Switch and** 1 x Power Button, 1 x Trigger Button **Buttons Mechanical and Environmental** AC/DC Adapter Input: 100 to 240V AC; Output: 5V DC, 3A **Battery Pack** Hot-swappable Battery, 3.8V, 4600mAh Enclosure ABS + PC Plastics Dimensions (H x W x D) 6.54 x 3.39 x 0.9 in/166 x 86 x 23 mm 0.71 lbs/320 g Weight MIL-STD-810G Durability FCC Class B, CE, RoHS Compliant Regulatory

The part of the pa	
Magnetic Stripe Reader	Triple Track Readers (ISO TK1, 2 & 3), JIS & AAMVA Compliant
Barcode Scanner	2D Barcode Scanner (Reads 1D and 2D)
Camera	8 MP Back Camera with Auto Focus, White Balance, Gain Control and Exposure Control
NFC/RFID Reader	HF 13.56MHz, ISO Standard 15693, 14443A(B) & 18000-3 Mode-1
GNSS	GPS
Mobile Broadband	4G LTE/AWS

Accessories



· Desktop Charging Cradle



· 4-Bay System Gang Charger



· Battery Pack





Temperature

Humidity

Operation: 14°F to 122°F (-10°C to 50°C);

Storage: -58°F to 158°F (-50°C to 70°C)

0% to 90% Non-Condensing

^{*} Specifications subject to change without notice.