



323MD Rugged Tablets

Slim, Antimicrobial, ANSI/AAMI ES60601-1 Certified Tablets for Efficient Operation

The 323MD Rugged Medical Tablet features the integration of a high-brightness 13.3" touchscreen and high-performance, energy-efficient Intel® Core™ processor within a slim, lightweight, durable package. With built-in back camera, Wi-Fi and BT connectivity, optional 2D barcode scanner, NFC/RFID Reader, front camera, and other optional data capture modules, this medical tablet serves as an effective tool to streamline the process of monitoring, recording, and retrieving patient data. The design of hot-swappable batteries enables continuous and stable operation during battery replacement, hence allowing healthcare professionals to work uninterrupted. Ideal for hospitals, clinics, and other healthcare facilities.





Features

- 13.3" LED-Backlit, sunlight-readable (1000 nits) touchscreen, digital pen support
- Intel® Core™ i5/i7 processor
- Microsoft® Windows® 10/11 IoT Enterprise operating system
- NIST compliant BIOS available
- IP65-rated for water and dust resistance
- MIL-STD-810H for shock and vibration protection
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- · Detachable keyboard option for 2-in-1 applications
- · Built-in 8 MP back camera
- Quick Access SSD

Major Options

- 2D Barcode Scanner (Reads 1D and 2D)
- 5MP Front Camera
- GPS Module
- · 4G/5G
- NFC/RFID Reader

Specifications



Model 323MD **System**

Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz CPU Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz

RAM 512GB to 1TB Flash

Storage *Support quick access SSD function to easily replace the SSD without opening the back cover.

Microsoft® Windows® 10/11 IoT Enterprise **Operating System** NIST Compliant BIOS Available

NIST Compliance 13.3" LED-Backlit, Sunlight Readable (1000 nits) Touchscreen Display

Display Resolution 1920 x 1080 8MP Back Camera Camera Speaker Built-In Speaker Microphone Built-In Microphone

Network Interface

WLAN Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band

ВТ

I/O Ports

USB Ports 1 x USB 3.0, 1 x latest USB/charging **Ethernet Port** 1 x Ethernet 10/100/1000MB Base-T LAN

DC IN

Switches and Buttons 1 x Power Button; 2 x Brightness Buttons; 5 x Programmable Buttons

Mechanical and Environmental

AC/DC Adapter Input: 100 to 240V AC; Output: 19V DC, 3.78A

Enclosure ABS + PC Plastic and Magnesium-Aluminum Alloy

Hot-swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-swappable Battery (11.4V, 5400mAh) **Battery Pack** (Optional) 90W Hot-swappable Battery, (11.4V, 8000mAh)

Dimensions (H x W x D) 12.8 x 10.7 x 0.8 in/325 x 273.5 x 20 mm

Weight 3.81 lbs/1.72 kg

Operation*: -10°C to 60°C (14°F to 140°F)

Optional -30°C to 60°C (-22°F to 140°F)
*For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F)

Temperature Storage: -55°C to 70°C (-67°F to 158°F)

Humidity 0% to 90% Non-Condensing

Certifications FCC/IC, CE/CB, ANSI/AAMI ES60601-1, RCM

IP65, MIL-STD-810H Certified Durability

Major Options

Barcode Scanner 2D Barcode Scanner (Reads 1D and 2D)

5MP Front Camera Camera

GNSS GPS

4G/5G Mobile Broadband

NFC/RFID Reader Dual Frequency(Reads 125 KHz and 13.56 MHz Credentials)

* Specifications subject to change without notice.



