



DA574LF

Medical-Grade All-in-One Computer

Slim Workstation for Point-of-Care Solutions

Designed for versatility in medical and healthcare applications, the DA574LF Medical All-in-One System offers optimal processing power and a range of options for diverse applications—from the high-performance Octa-core processor for demanding workloads to cost-efficient configurations ideal for nurse stations. Featuring a 23.8" full-HD touchscreen, a fanless design and antimicrobial enclosure, and VESA mounting compatibility, this slim and energy-efficient system seamlessly integrates into clean-sensitive environments. Optional features such as a smart card/CAC reader, RFID reader, and 5 MP front MIPI camera further enhance workflow efficiency, creating a robust solution for patient data management, telemedicine, and point-of-care applications.



Features

- 23.8" full-HD (1920 × 1080) touchscreen
- Qualcomm® Octa-core processor
- Android 14 operating system
- Space-saving all-in-one, slim, fanless design with antimicrobial enclosure
- VESA mounting compatibility for easy installation and optimized mobility
- IP65-rated front panel with IP54-rated enclosure
- Integrated hot-swappable batteries (optional, up to 2 batteries)

Major Options

- 5 MP front MIPI camera
- Smart card/CAC reader
- RFID reader

Specifications



Model	DA574LF
--------------	----------------

System

CPU	Qualcomm® Octa-core (up to 2.7 GHz)
RAM	8GB LPDDR4X
Storage	128GB UFS 2.2
Operating System	Android 14
Display	23.8"
Touchscreen	P-CAP touch
Brightness	250cd/m2
Contrast Ratio	1000:1
Display Resolution	Full-HD (1920 x 1080)
Buttons	1 x power button, 4 x programmable buttons
Speaker	2 x 5W speakers
Microphone	Built-in microphone array

Network Interface

WLAN	Wi-Fi 802.11ax, 2.4GHz/5GHz dual band
BT	5.2

I/O Ports

USB Port	3 x USB 3.2 Gen 1 (Type-A) (for display output and charging)
Ethernet Port	1 x GbE LAN (10/100/1000 Base-T)
COM	1
DC-In Jack	1
SIM Card Slot	1 (supports dual SIM)
POAG (optional)	1

Mechanical and Environmental

Fan/Fanless	Fanless
Battery Pack	(Optional) 2 x Li-ion batteries (8250mAh, 90Wh)
AC/DC Adapter	Input: 100 to 240V AC; Output: 19V DC, 6.31A
Enclosure	ABS plastic, antimicrobial enclosure
Dimensions (H x W x D)	14.49 x 22.4 x 1.67 in/368 x 569 x 42.5 mm
Weight	16.31 lbs/7.4 kg
VESA	100 x 100 mm
Water Resistance	IP65 sealed front bezel and IP54 back cover enclosure
Temperature	Operation: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 60°C (-4°F to 140°F)
Humidity	0% to 90% non-condensing

Major Options

Camera	5 MP front MIPI camera
Smart Card/CAC Reader	Half-slot (ISO 7816 T=0, T=1 and 1.8/3/5V smart card)
RFID Reader	HF 13.56 MHz, ISO 15693, 14443A(B) and 18000-3 Mode 1, or Dual Frequency (125 kHz and 13.56 MHz)

*Specifications subject to change without notice.

Accessories

- Desktop Stand

