



| Model | DT362GL | DT362D | DT382GL | DT382DN |
|-------|---------|--------|---------|---------|
|-------|---------|--------|---------|---------|

System

| | | | | |
|--------------------------------|--|---|---|---|
| CPU | Intel® Pentium® Silver 4-Core, 1.1 GHz (up to 2.7 GHz) | DT362DN: Intel® N200, 4-core (up to 3.70 GHz) DT362DH: Intel® Core™ i3-N300, 8-core (up to 3.80 GHz) | Intel® Pentium® Silver 4-Core, 1.1 GHz (up to 2.7 GHz) | Intel® N200, 4-core (up to 3.70 GHz) |
| RAM | 8GB | 16GB | 8GB | 16GB |
| Storage | 256GB flash | 512GB | 512GB | 512GB |
| Operating System | Microsoft® Windows® 10/11 IoT Enterprise | Microsoft® Windows® 11 IoT Enterprise | Microsoft® Windows® 10/11 IoT Enterprise | Microsoft® Windows® 11 IoT Enterprise |
| NIST Compliance | NIST Compliant BIOS Available | | | |
| Display | 6" LED-Backlight (350 nits) screen with capacitive touch | 6" LED-Backlit (850 nits) touchscreen | 8" LED-Backlit, High-Brightness (800 nits) Touchscreen | 8" LED-Backlit, High-Brightness (800 nits) Touchscreen |
| Display Resolution | 720 x 1440 | 2160 x 1080 (2K) | 1280 x 800 | 1280 x 800 |
| Fan/Fanless | Fanless | Fanless | Fanless | Fanless |
| Switches and Buttons | 1 x Power Button, 2 x Trigger Buttons | 1 x Power Button, 2 x Trigger Buttons | 1 x Power Button, 2 x Trigger Buttons, 2 x Brightness Buttons, 4 x Programmable Buttons | 1 x Power Button, 2 x Trigger Buttons, 2 x Brightness Buttons, 4 x Programmable Buttons |
| Microphone | Built-In Microphone | Built-In Microphone | Built-In Microphone | Built-In Microphone |
| Speaker | Built-In Speaker | Built-In Speaker | Built-In Speaker | Built-In Speaker |
| Trusted Platform Module | fTPM 2.0 | fTPM 2.0 | fTPM 2.0 | fTPM 2.0 |

Network Interface

| | | | | |
|-------------|-------------------------------------|--|-------------------------------------|--|
| WLAN | Wi-Fi 802.11ac, 2.4/5 GHz Dual Band | Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band | Wi-Fi 802.11ac, 2.4/5 GHz Dual Band | Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band |
| BT | 4.2 LE | 5.3 | 4.2 LE | 5.3 |

I/O Ports

| | | | | |
|------------------------------|---|---|--------------------------------------|--|
| USB Port | 1 x latest USB/charging | 1 x latest USB/charging | 1 x USB 3.0, 1 x latest USB/charging | 1 x USB 3.0, 1 x latest USB/charging |
| Headset Jack | N/A | N/A | 1 (3.5 mm) | 1 (3.5 mm) |
| DC-In | N/A | N/A | 1 | 1 |
| Ethernet | N/A | N/A | N/A | N/A |
| SD Slot | N/A | DT362DN:1 x Micro SD Card Slot DT362DH:N/A | 1 x Micro SD Card Slot | 1 x Micro SD Card Slot |
| Smart Card/CAC Reader | Full Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card | Full Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card | N/A | Half-slot (Reads ISO 7816 T=0, T=1; 1.8 / 3 / 5V Smart Card(Optional)) |
| SIM Card Slot | N/A | N/A | 1 x NANO SIM Slot | 1 x NANO SIM Slot |

Mechanical and Environmental

| | | | | |
|---|---|---|---|---|
| AC/DC Adapter | Input: 100 to 240V AC; Output: 20V DC, 3.25A | Input: 100 to 240V AC; Output: 20V DC, 3.25A | Input: 100 to 240V AC; Output: 19V DC, 3.42A | Input: 100 to 240V AC; Output: 19V DC, 3.42A |
| Battery Pack | Hot-Swappable Battery (3300mAh) | Hot-Swappable Battery (2700mAh) | Hot-Swappable Battery (7.6V, 6000mAh) Hot-Swappable Battery (11.4V, 5400mAh) (Optional) Hot-Swappable Battery (11.4V, 8000mAh) (Optional) | Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh) (Optional) |
| Enclosure | ABS + PC Plastic | | | |
| Dimensions (H x W x D) | 7.6 x 3.7 x 1.2 in/192 x 95 x 31 mm | 7.6 x 3.7 x 1.2 in/192 x 95 x 31 mm | 5.8 x 9.2 x 1.1 in/147.3 x 234 x 27.7 mm | 5.8 x 9.2 x 1.1 in/147.3 x 234 x 27.7 mm |
| Weight | 1.1 lbs/485 g | 1.1 lbs/485 g | 2.43 lbs/1.1 kg | 2.43 lbs/1.1 kg |
| Durability | IP65, MIL-STD-810H and MIL-STD-461G Certified, Class 1, Division 2, Groups A, B, C and D (Optional) | IP65, MIL-STD-810H and MIL-STD-461G Certified | IP65, MIL-STD-810H and MIL-STD-461G Certified | IP65, MIL-STD-810H Certified |
| Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing | Yes | Yes | Yes | Yes |
| Regulatory | FCC Class B, RoHS Compliant | FCC Class B, RoHS Compliant | FCC Class B, RoHS Compliant | FCC Class B, RoHS Compliant |
| Temperature | Operation: -10°C to 50°C (14°F to 122°F); Storage: -50°C to 70°C (-58°F to 158°F) | | | |
| Humidity | 0% to 90% Non-Condensing | | | |

Major Options

| | | | | |
|-----------------------------------|---|--|---|--|
| Camera | 8MP Back Camera | 5 MP Front USB Camera and 8 MP Back USB Camera | 8 MP Back Camera with Auto Focus, White Balance, Gain Control, and Exposure Control | 8 MP Back Camera with Auto Focus, White Balance, Gain Control, and Exposure Control |
| Long Range Barcode Scanner | Read range of 4 in (10cm) to 66 ft. (20.11m) | Read range of 4 in (10cm) to 66 ft. (20.11m) | N/A | Read range of 4 in (10cm) to 66 ft. (20.11m) |
| Barcode Scanner | 2D Barcode Scanner (Reads 1D and 2D) | 2D Barcode Scanner (Reads 1D and 2D) | 2D Barcode Scanner (Reads 1D and 2D) | 2D Barcode Scanner (Reads 1D and 2D) |
| GNSS Module | GPS Module | | | |
| NFC/RFID Reader | HF 13.56 MHz, ISO 15693, 14443A(B), 18000-3 Mode 1 | | | |
| UHF RFID Reader | 865 to 928 MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; Reading Distance of 16 ft (4.87 m) with Integrated ThingMagic Micro Module and Embedded Antenna; Reading Range of 30 ft (9.1 m) with Trigger Grip Antenna | | 865 to 928 MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; Reading Distance of 16 ft (4.87 m) with Integrated ThingMagic Micro Module and Embedded Antenna; Reading Range of 30 ft (9.1 m) with Trigger Grip Antenna | 865 to 928MHz, EPCglobal Class 1 Gen 2/ ISO 18000-6C; 16 ft (4.87m) Reading Distance |
| Long-Range BT | Class 1 BT (1000 ft) | N/A | Class 1 BT (1000 ft) | Class 1 BT (1000 ft) |
| Mobile Broadband | N/A | N/A | N/A | 4G LTE/AWS |

* Specifications subject to change without notice.



| Model | DT381RP | DT340T |
|-------|---------|--------|
|-------|---------|--------|

System

| | | |
|----------------------|--|--|
| CPU | Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ i7-1355U, 10-Core, up to 5 GHz | Intel® Core™ i5-1340P, 12-Core, up to 4.6 GHz Intel® Core™ i7-1370P, 14-Core, up to 5.2 GHz |
| RAM | 16GB | 64GB |
| GPU | N/A | NVIDIA RTX A1000 or RTX A2000 graphics card |
| Storage | 512GB to 1TB SSD | 512GB to 2TB Flash |
| Operating System | Microsoft® Windows® 10/11 IoT Enterprise Enterprise | Microsoft® Windows® 10/11 IoT Enterprise, 64bit or Ubuntu |
| NIST Compliance | NIST Compliant BIOS Available | |
| Display | 8" LED-Backlit, High-Brightness (800 nits) Touchscreen | 14" LED-Backlit, High-Brightness (1,000 nits) Touchscreen with Multi-Touch |
| Display Resolution | 1280 x 800 | 1920 x 1080 |
| Fan/Fanless | Fanless | Fanless |
| Switches and Buttons | 1 x Power Button, 2 x Brightness Buttons, 4 Programmable Buttons | 1 x Power Button, 2 x Programmable Buttons |
| Microphone | N/A | Built-In Microphone with DSP for Real-Time Video Streaming |
| Speaker | Built-In Speaker | Built-In Speaker |

Network Interface

| | | |
|------|-------------------------------------|---------------------------------------|
| WLAN | Wi-Fi 802.11ax, 2.4/5 GHz Dual Band | Wi-Fi 802.11ax 2.4/5/6 Ghz three band |
| BT | 5.2 | 5.2 |

I/O Ports

| | | |
|-----------------------|--|---|
| USB Port | 1 x USB 3.2 Gen 1 Type A, 1 x latest USB/charging | 1 x USB 3.0, 2 x USB 2.0 |
| Headset Jack | 1 (3.5 mm) | 1 (3.5 mm) |
| DC-In | 1 | 1 |
| Ethernet | 1 x Ethernet 10/100/1000MB Base-T LAN | 1 x Ethernet 10/100/1000MB Base-T LAN |
| SD Slot | 1 x Micro SD Card Slot | N/A |
| Smart Card/CAC Reader | Full Slot (reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card | Full-Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card |
| SIM Card Slot | N/A | |

Mechanical and Environmental

| | | |
|--|--|---|
| AC/DC Adapter | Input: 100 to 240V AC; Output: 19V DC, 3.25A | Input: 100 to 240V AC; Output: 19V 65W for w/o GPU SKU and 19V 120W for A1000 SKU |
| Battery Pack | Hot-Swappable Battery (7.6V, 6000mAh) Optional: Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh) | 2 x Hot-swappable Battery (11.4V, 5400mAh) 2 x Hot-swappable Battery (11.4V, 8000mAh)(Optional) |
| Enclosure | ABS + PC Plastic | ABS + PC Plastic and Magnesium-Aluminum Alloy |
| Dimensions (H x W x D) | 5.8 x 9.2 x 1.0 in/147.3 x 234 x 25.5 mm | 9.6 x 14.8 x 1.16 in/244 x 376 x 29.5 mm |
| Weight | 2.65 lbs/1.2 kg | 6.38 lbs/2.9 kg |
| Durability | IP65, MIL-STD-810H and MIL-STD-461G Certified | IP65, MIL-STD-810H and MIL-STD-461G Certified |
| Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing | Yes | Yes |
| Regulatory | FCC Class B, CE, RoHS, Energy Star 8.0 Compliant | FCC Class B, CE, RoHS, Energy Star 8.0 Compliant |
| Temperature | Operation: AC Mode: -20°C to 45°C (-4°F to 113°F) Battery Mode: 0°C to 40°C (32°F to 104°F) Optional Wider Operating Temperature Range: -30°C to 40°C (-22°F to 104°F) Storage: -50°C to 70°C (-58°F to 158°F) | Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810H method 501.7, Procedure II, and method 502.7, Procedure II *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C to 50°C (32°F to 122°F) Storage: -50°C to 70°C (-58°F to 158°F) |
| Humidity | | |

Major Options

| | | |
|----------------------------|--|---|
| Camera | 8 MP Front and Back Cameras w/ Auto Focus, White Balance, Gain Control, and Exposure Control | 8 MP Back Camera with Flash |
| Long Range Barcode Scanner | N/A | N/A |
| Barcode Scanner | N/A | N/A |
| GNSS | GPS | |
| NFC/RFID Reader | N/A | N/A |
| UHF RFID Reader | N/A | N/A |
| Mobile Broadband | 4G LTE/AWS | 4G LTE/AWS |
| Long-Range BT | Class 1 BT (1000 ft) | N/A |
| ANTENNA | N/A | Dual pass through antennas integrated in the docking cradle |
| GPU | N/A | Integrated graphics card, NVIDIA RTX A1000 or RTX A2000 |

* Specifications subject to change without notice.



| Model | DT302RP | DT312RP | DT323RP |
|-------|---------|---------|---------|
|-------|---------|---------|---------|

System

| | | | |
|-----------------------------|---|---|---|
| CPU | Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz | Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz | Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz |
| RAM | 8GB to 32GB | 8GB | 8GB |
| Storage | 512GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover | 512GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover | 512GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover |
| Operating System | Microsoft® Windows® 10/11 IoT Enterprise | Microsoft® Windows® 11 IoT Enterprise | Microsoft® Windows® 11 IoT Enterprise |
| NIST Compliance | NIST Compliant BIOS Available | | |
| Display | 10.1" LED-Backlit, Sunlight-Readable (800 nits) Touchscreen LCD | 11.6" LED-Backlit, Sunlight-Readable (1000 nits) Touchscreen | 13.3" LED-Backlit, Sunlight-Readable (1000 nits) Touchscreen |
| Display Resolution | 1920 x 1200 | 1920 x 1200 | 1920 x 1080 |
| Fan/Fanless | Fanless | Fanless | Fanless |
| Switches and Buttons | 1 x Power Button, 2 x Brightness Buttons, 5 x Programmable Buttons | 1 x Power Button, 2 x Brightness Buttons, 5 x Programmable Buttons | 1 x Power Button; 2 x Brightness Buttons; 5 x Programmable Buttons |
| Microphone | Built-In Microphone | Built-In Microphone with DSP for Real-Time Video Streaming | Built-In Microphone |
| Speaker | Built-In Speaker | Built-In Speaker | Built-In Speaker |
| Camera | 5 MP Front Camera and 8 MP Back Camera (Options) | 5 MP Front Camera and 8 MP Back Camera (Options) | 5 MP Front Camera and 8 MP Back Camera (Options) |

Network Interface

| | | | |
|-------------|---------------------------------------|--|--|
| WLAN | Wi-Fi 802.11ax 2.4/5/6 GHz three band | Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band | Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band |
| BT | 5.2 | 5.2 | 5.3 |

I/O Ports

| | | | |
|------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| USB Port | 1 x USB 3.0, 1 x latest USB/charging | 1 x USB 3.0, 1 x latest USB/charging | 1 x USB 3.0, 1 x latest USB/charging |
| Headset Jack | 1 (3.5 mm) | 1 (3.5 mm) | 1 (3.5 mm) |
| DC-In | 1 | 1 | 1 |
| Ethernet | 1 x Ethernet 10/100/1000MB Base-T LAN | 1 x Ethernet 10/100/1000MB Base-T LAN | 1 x Ethernet 10/100/1000MB Base-T LAN |
| SD Slot | 1 x Micro SD Card Slot | N/A | N/A |
| Smart Card/CAC Reader | N/A | N/A | N/A |

Mechanical and Environmental

| | | | |
|---|---|--|--|
| AC/DC Adapter | Input: 100 to 240V AC; Output: 19V DC, 3.42A | Input: 100 to 240V AC; Output: 19V DC, 3.42A | Input: 100 to 240V AC; Output: 19V DC, 3.42A |
| Battery Pack | Hot-Swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-Swappable Battery (11.4V, 5400mAh) (Optional) 90W Hot-Swappable Battery, (11.4V, 8000mAh) | Hot-Swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-Swappable Battery (11.4V, 5400mAh) (Optional) 90W Hot-Swappable Battery, (11.4V, 8000mAh) | Hot-Swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-Swappable Battery (11.4V, 5400mAh) (Optional) 90W Hot-Swappable Battery, (11.4V, 8000mAh) |
| Enclosure | ABS + PC Plastic and Magnesium-Aluminum Alloy | ABS + PC Plastic and Magnesium-Aluminum Alloy | ABS + PC Plastic and Magnesium-Aluminum Alloy |
| Dimensions (H x W x D) | 7.7 x 10.71 x 0.79 in/195.6 x 272 x 20 mm | 8.3 x 12.4 x 0.78 in/212 x 316 x 20 mm | 12.8 x 10.7 x 0.8 in/325 x 273.5 x 20 mm |
| Weight | 3 lbs/1.32 kg | 3.43 lbs/1.55 kg | 3.81 lbs/1.72 kg |
| Durability | IP65, MIL-STD-810H and MIL-STD-461G Certified | IP65, MIL-STD-810H and MIL-STD-461G Certified | IP65, MIL-STD-810H Certified |
| Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing | Yes | Yes | Yes |
| Regulatory | CE, FCC Class B, RoHS, Energy Star 8.0 Compliant | FCC Class B, CE, RoHS Compliant | FCC Class B, CE, RoHS Compliant |
| Temperature | Operation: -10°C to 60°C (14°F to 140°F); *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C to 50°C (32°F to 122°F) *When use DT302 with AC power adapter, to comply with safety regulation, the recommended usage temperature is from 0°C to 40°C Storage: -50°C to 70°C (-58°F to 158°F) | Operation*: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C to 50°C (32°F to 122°F) Storage: -50°C to 70°C (-58°F to 158°F) | Operation*: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C to 50°C (32°F to 122°F) Storage: -55°C to 70°C (-67°F to 158°F) |
| Humidity | 0% to 90% Non-Condensing | 0% to 90% Non-Condensing | 0% to 90% Non-Condensing |

Major Options

| | | | |
|-------------------------|--|--|---|
| Camera | 5 MP Front Camera and 8 MP Back Camera | 5 MP Front Camera and 8 MP Back Camera | 5 MP Front Camera and 8 MP Back Camera |
| Barcode Scanner | 2D Barcode Scanner (Reads 1D and 2D) | 2D Barcode Scanner (Reads 1D and 2D) | 2D Barcode Scanner (Reads 1D and 2D) |
| GNSS | U-blox M9N GNSS Module | U-blox M9N GNSS Module | GPS Module with Concurrent Reception of GPS and GLONASS; Industry Leading - 167dBm Navigation Sensitivity |
| Mobile Broadband | 4G/5G | 4G LTE/AWS | 4G/5G |

* Specifications subject to change without notice.

Rugged Tablets



| Model | DT301Y | DT301YR | DT311YR |
|-------|--------|---------|---------|
|-------|--------|---------|---------|

System

| | | | |
|----------------------|--|--|---|
| CPU | Intel® Pentium® Gold 7505, 2-Core, up to 3.5 GHz | Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz | |
| RAM | 8GB to 32GB | | |
| Storage | 512GB to 2TB Flash | 512GB to 2TB Flash | 512GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover |
| Operating System | Microsoft® Windows® 10/11 IoT Enterprise | | |
| NIST Compliance | NIST Compliant BIOS Available | | |
| Display | 10.1" LED-Backlit, High-Brightness (1000 nits) Touchscreen | 10.1" LED-Backlit, High-Brightness (1000 nits) Touchscreen | 11.6" LED-Backlit, High-Brightness (1000 nits) Touchscreen |
| Display Resolution | 1920 x 1200 | 1920 x 1200 | 1920 x 1080 |
| Fan/Fanless | Fanless | | |
| Switches and Buttons | 1 x Power Button, 2 x Brightness Buttons, 5 x Programmable Buttons | 1 x Power Button; 2 x Brightness Buttons; 5 x Programmable Buttons | |
| Microphone | Built-In Microphone | | |
| Speaker | Built-In Speaker | | |

Network Interface

| | | | |
|------|-------------------------------------|-------------------------------------|--|
| WLAN | Wi-Fi 802.11ax, 2.4/5 GHz Dual Band | Wi-Fi 802.11ax, 2.4/5 GHz Dual Band | |
| BT | 5.2 | | |

I/O Ports

| | | | |
|-----------------------|--|---|--|
| USB Port | 1 x USB 3.0, 1 x latest USB/charging | 1 x USB 3.0, 1 x latest USB/charging | |
| Headset Jack | 1 (3.5 mm) | 1 (3.5 mm) | |
| DC-In | 1 | 1 | |
| Ethernet | 1 | 1 x Ethernet 10/100/1000MB Base-T LAN | |
| Smart Card/CAC Reader | Full Slot (reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card | Full-Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card | |

Mechanical and Environmental

| | | | |
|--|--|--|--|
| AC/DC Adapter | Input: 100 to 240V AC; Output: 19V DC, 3.42A | Input: 100 to 240V AC; Output: 19V DC, 3.42A | Input: 100 to 240V AC; Output: 20V DC, 3.25A |
| Battery Pack | Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh) (Optional) | Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh)(Optional) | |
| Enclosure | ABS + PC Plastic and Magnesium-Aluminum Alloy | | |
| Dimensions (H x W x D) | 7.8 x 11 x 0.86 in/198 x 280 x 21.9 mm | 7.8 x 11 x 0.86 in/198 x 280 x 21.9 mm | 8.3 x 12.4 x 0.86 in/212 x 316 x 21.9 mm |
| Weight | 3.1 lbs/1.4 kg | 3.1 lbs/1.4 kg | 3.5 lbs/1.6 kg |
| Durability | IP65, MIL-STD-810H and MIL-STD-461G Certified | | |
| Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing | Yes | Yes | Yes |
| Regulatory | FCC Class B, CE, RoHS, Energy Star 8.0 Compliant | | |
| Temperature | Operation: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C to 50°C (32°F to 122°F) | Operation: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C to 50°C (32°F to 122°F) | Operation: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C to 50°C (32°F to 122°F) |
| | Storage: -50°C to 70°C (-58°F to 158°F) | Storage: -50°C to 70°C (-58°F to 158°F) | |
| Humidity | 0% to 90% Non-Condensing | | |

Major Options

| | | | |
|------------------|---|---|--|
| Camera | 2 MP Front Camera and 8 MP Back Camera | 2 MP Front Camera and 8 MP Back Camera | |
| Barcode Scanner | 2D Barcode Scanner (Reads 1D and 2D) | 2D Barcode Scanner (Reads 1D and 2D) | |
| GNSS | GPS | | |
| UHF RFID Reader | 865 to 928MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 30 ft (9.14m) Reading Distance | 865 to 928MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 30 ft (9.14m) Reading Distance | |
| Mobile Broadband | 4G LTE/AWS | | |
| Long-Range BT | Class 1 BT (1000 ft) | | |

* Specifications subject to change without notice.

