

4-Bay Battery Gang Charger

BASIC OPERATION GUIDE

Thank you for purchasing the 4-Bay Battery Gang Charger by DT Research. The 4-Bay Battery Gang Charger (ACC-001-33THK) is capable of charging up to four battery packs for the Mobile Tablets. The package includes one 4-Bay Battery Gang Charger, one AC-DC adapter, and one power cord. The 4-Bay Battery Gang Charger features a DC-input jack, four battery charging slots, and four LED lights that indicate charging status.



Instructions

Connect the AC-DC adapter cable to the DC-input jack. Insert a battery pack into each bay, correctly lining up the connector pins. After inserting the battery pack into the bay, the LED light will indicate charging (yellow). When charging is complete or if the battery pack is already fully charged, the LED will be green.



CAUTION:

This charger must only be used with the specific battery models for which it is designed. Failure to do so may result in battery or charger damage, or personal injury.

LED Indicator Status

Each charging bay features an LED light in front of it to indicate the battery charge status.

- Power On/Off: LED off
- Battery Fully Charged: Green
- Charging Battery: Yellow

Package Contents

- One 4-Bay Battery Gang Charger
- One AC-DC adapter with power cord
- Basic operation guide



Precautions

- Always exercise care when operating and handling.
- Do not disassemble any portion of the charger and adapter as this will void any product warranty.
- Do not use any power adapter other than the one provided with the device or acquired from the manufacturer or its partners.
- In the unlikely event that abnormal noise, strange odor, or smoke is present, immediately disconnect all power sources. Please report the problem to your device provider immediately

Specifications

I/O Ports	
DC-in	1
Charging Slot	4
Mechanical and Environmental	
AC/DC Adapters	Input: 100 – 240V AC; Output: 12V DC, 3.33A
Dimensions	2in (H) x 7.3in (W) x 6.4in (D)
Weight	1.2 lbs
Regulatory	FCC Class B, CE, RoHS compliant
Temperature	Operation: 0°C – 35°C; Storage: -20°C – 60°C
Humidity	0% – 90% non-condensing

* Specifications subject to change without notice.