



RUGGED 2-IN-1 MEDICAL TABLETS

Slim, Antimicrobial, ANSI/AAMI ES60601-1 Certified Tablet for Efficient Operations

The DT Research Rugged 2-in-1 Medical Tablets feature the integration of brilliant capacitive touch screens and high performance, energy-efficient Intel[®] Core[™] i series processors within slim, lightweight, durable packages. With built-in front and back cameras, Wi-Fi as well as optional data capture modules, these medical tablets offer health professionals effective tools to monitor, record and retrieve patient information.





Features

- 10.1" or 13.3" high-brightness capacitive screens, digital pen support
- Intel[®] 8th or 10th Generation Core[™] i processor
- Microsoft[®] Windows[®] 10 IoT Enterprise or Ubuntu operating system
- Docking keyboard option for 2-in-1 (tablet/ laptop) applications
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- IP65 and MIL-STD-810G certified
- NIST compliant BIOS available
- Energy Star 8.0 certified (301Y/MD)
- Hot swappable battery pack
- Built-in front and back cameras
- Built-in smart card/CAC reader

Major Options

- Barcode scanner
- Single/dual frequency NFC/RFID reader
- 4G LTE/AWS

Specifications





301Y/MD

System

Model

System			
CPU	Intel® Core™ i5-8250U, Quad-Core, 1.6GHz (up to 3.4GHz) Intel® Core™ i7-8550U, Quad-Core, 1.8GHz (up to 4.0GHz) Intel® Core™ i7-10710U, Hexa-Core, 1.1GHz (up to 4.7GHz)		
RAM	8GB to 16GB	8GB to 16GB	
Storage	256GB to 512GB Flash	256GB to 512GB Flash	
Operating System	Microsoft® Windows® 10 IoT Enterprise or Ubuntu		
NIST Compliance	NIST compliant BIOS available		
Display	10.1" LED-backlight, high-brightness (800 nits) screen with capacitive touch, outdoor viewable	13.3" LED-backlight, high-brightness (1000 nits) screen with capacitive touch, outdoor viewable	
Display Resolution	1920 × 1200	1920 x 1080	
Buttons	1 power button, 2 brightness control buttons, 5 programmable buttons	1 power button, 2 brightness control buttons, 5 programmable buttons	
Microphone	Built-in microphone	Built-in microphone	
Speaker	Built-in speaker	Built-in speaker	
Camera	Full-HD front camera and 8 megapixel back camera	Full-HD front camera and 8 megapixel back camera	
Network Interface			

 WLAN
 Wi-Fi 802.11ax, 2.4GHz/ 5GHz dual band

 I/O Ports
 USB 3.0 x 1, USB Type C x 1 (data transmitting and charging)
 USB 3.0 x 3, USB Type C x 1 (data transmitting and charging)

 Headset Jack
 1 (3.5mm)
 1 (3.5mm)

 Ethernet Port
 Ethernet 10/100/1000MB Base-T LAN
 Ethernet 10/100/1000MB Base-T LAN

Smart Card/ CAC ReaderFull-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart cardFull-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card

Mechanical and Environmental

AC/DC Adapter	Input: 100-240V AC; Output: 20V DC, 3A		
Battery Pack	Hot swappable battery, 11.4V, 5400mAh	Hot swappable battery, 11.4V, 5400mAh	
Enclosure	ABS + PC plastics and magnesium-aluminum alloy; antimicrobial enclosure		
Dimensions (H x W x D)	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm	10.1 x 13.2 x 0.8 in/ 256 x 335 x 21 mm	
Weight	3.1 lbs/ 1.4 kg	3.97 lbs/ 1.8 kg	
Durability	IP65 and MIL-STD-810G certified	IP65 and MIL-STD-810G certified	
Regulatory	FCC/IC, CE/CB, RCM, CCC, ANSI/AAMI ES60601-1, Energy Star 8.0	FCC/IC, CE/CB, RCM, CCC, ANSI/AAMI ES60601-1	
Temperature	Operation*: -10°C to 60°C (14°F to 140°F), optional -30°C to 60°C (-22°F to 140°F) Storage: -55°C to 70°C (-67°F to 158°F) * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F)		
Humidity	0% – 90% non-condensing		

Major Options

Barcode Scanner	2D scanner, reads 1D also	2D scanner, reads 1D also
NFC/RFID Reader	HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1	Dual frequency, reads both 125KHz and 13.56MHz credentials
Mobile Broadband	4G LTE/AWS	4G LTE/AWS

* Specifications subject to change without notice.

Accessories





DT Research, Inc. 2000 Concourse Drive, San Jose, CA 95131 Copyright © 2022, DT Research, Inc. All Rights Reserved.

031122 DT300MD EN

www.dtresearch.com/productconfig