



301Y/MD Rugged 2-in-1 Medical Tablet

Slim, Antimicrobial, ANSI/AAMI ES60601-1 Certified Tablet for Efficient Operations

The 301Y/MD Rugged 2-in-1 Medical Tablet features the integration of a brilliant 10.1" capacitive touchscreen and a high-performance, energy-efficient Intel® Core™ i series processor within a slim, lightweight, durable package. With built-in front and back cameras, Wi-Fi, and other optional data capture modules, this medical tablet offers health professionals an effective tool to monitor, record and retrieve patient information.





Features

- 10.1" Full-HD capacitive touchscreen, 800 nits, supports digital pen
- Intel[®] Core[™] i7/i5 processor
- Microsoft® Windows® 10/11 IoT Enterprise or Ubuntu OS
- · NIST compliant BIOS available
- Hot-swappable battery pack
- Built-in front & back cameras and smart card/CAC reader
- Docking keyboard option for 2-in-1 (tablet/laptop) applications
- IP65-rated for water and dust resistance
- MIL-STD-810G for shock and vibration protection
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- · Energy Star 8.0 certified

Major Options

- · Barcode scanner
- NFC/RFID reader
- · 4G LTE/AWS

Specifications



Model	301Y/MD
System	
СРИ	Intel® Core™ i5-1135G7, 4-Core, up to 4.2 GHz Intel® Core™ i7-1165G7, 4-Core, up to 4.7 GHz
RAM	8GB to 16GB
Storage	256GB to 512GB Flash
Operating System	Microsoft® Windows® 10/11 IoT Enterprise or Ubuntu
NIST Compliance	NIST Compliant BIOS Available
Display	10.1" LED-Backlit, High-Brightness (800 nits) Touchscreen
Display Resolution	1920 x 1200
Speaker	Built-In Speaker
Microphone	Built-In Microphone

5 MP Front Camera & 8 MP Back Cameras

Network Interface

WLAN Wi-Fi 802.11ax, 2.4/5 GHz Dual Band

I/O Interfaces

Camera

USB Ports	1 x USB 3.0, 1 x USB Type-C
Headphone Jack	1 (3.5mm)
Ethernet Port	1 (RJ45)
DC-in	1
Smart Card/CAC Reader	Full Slot (Reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card
Switches and Buttons	1 x Power Button, 2 x Brightness Buttons, 5 x Programmable Buttons

Mechanical and Environmental

AC/DC Adapter	Input: 100-240V AC; Output: 20V DC, 3A
Battery Pack	Hot-Swappable Battery (5400mAh)
Enclosure	ABS + PC Plastic and Magnesium-Aluminum Alloy; Antimicrobial Enclosure
Dimensions (H x W x D)	7.8 x 11 x 0.86 in/198 x 280 x 21.9 mm
Weight	3.1 lbs/1.4 kg
Durability	IP65 and MIL-STD-810G Certified
Regulatory	FCC/IC, CE/CB, RCM, ANSI/AAMI ES60601-1, Energy Star 8.0
Temperature	Operation*: -10°C \sim 60°C (14°F \sim 140°F), optional -30°C \sim 60°C (-22°F \sim 140°F) *For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C \sim 45°C (14°F \sim 113°F) Storage: -55°C \sim 70°C (-67°F \sim 158°F)
Humidity	0% ~ 90% Non-Condensing

Major Options

Barcode Scanner	2D Barcode Scanner (Reads 1D & 2D)
NFC/RFID Reader	HF 13.56 MHz, ISO 15693, 14443A(B) & 18000-3 Mode 1
Mobile Broadband	4G LTE/AWS

^{*} Specifications subject to change without notice.

Accessories





Docking Keyboard



Slim Detachable Keyboard



Handstrap with Kickstand



Desktop Charging Cradle





Battery Pack

3-Slot Battery Holster





Digital Pen



Battery Charging Kits







www.dtresearch.com/productconfig

Product Configurator