



## 306Q POS Tablet

### Rugged, Multi-functional for Point-of-Service/Sales Applications

The 306Q POS Tablet integrates a 6" capacitive touch screens, Qualcomm octa-core processor and Android operating system in a compact and robust packages for point-of-service/sale applications, inventory management, and field applications. Emphasizing superior integration and handling, the 306Q offers embedded POS-centric peripherals including magnetic stripe reader, barcode scanner, NFC/RFID reader, as well as back camera to provide accurate data collection and service efficiency in the restaurant, on the sales floor, and in the casinos and resorts.



### Features

- 6" LED-backlight screen with capacitive touch, digital pen support
- Qualcomm octa-core processor
- Android operating system
- NIST compliant BIOS available
- Built-in back camera
- MIL-STD-810G for shock and vibration protection
- Hot swappable battery pack

### Major Options

- Magnetic stripe reader
- Barcode scanner
- NFC/RFID reader
- GPS
- 4G LTE/AWS

# Specifications

## System

<b>CPU</b>	Qualcomm Octa-Core, 2.0GHz
<b>RAM</b>	4GB
<b>Storage</b>	64GB flash
<b>Operating System</b>	Android 9.0 and 10
<b>NIST Compliance</b>	NIST compliant BIOS available
<b>Display</b>	6" LED-backlight screen with capacitive touch
<b>Display Resolution</b>	720 x 1440
<b>Camera</b>	8 megapixel back camera with auto focus, white balance, gain control and exposure control
<b>Control Switch and Buttons</b>	1 power button, 2 trigger buttons

## Network Interface

<b>WLAN</b>	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band
-------------	--

## I/O Ports

<b>USB Ports</b>	USB Type-C x 1
<b>SD Slot</b>	1 micro SD card slot

## Mechanical and Environmental

<b>AC/DC Adapter</b>	Input: 100-240V AC; Output: 5V DC, 3A
<b>Battery Pack</b>	Hot swappable battery, 3.8V, 4600mAh
<b>Enclosure</b>	ABS + PC plastics
<b>Dimensions (H x W x D)</b>	6.54 x 3.39 x 0.9 in/ 166 x 86 x 23 mm
<b>Weight</b>	0.71 lbs/ 320 g
<b>Durability</b>	MIL-STD-810G
<b>Regulatory</b>	FCC Class B, CE, RoHS compliant
<b>Temperature</b>	Operation: 14°F to 122°F (-10°C to 50°C); Storage: -4°F to 140°F (-20°C to 60°C)
<b>Humidity</b>	0% – 90% non-condensing

\* Specifications subject to change without notice.

## Major Options

<b>Magnetic Stripe Reader</b>	Triple track readers (ISO TK1, 2 & 3), JIS & AAMVA compliant
<b>Barcode Scanner (2D)</b>	2D scanner, reads 1D also
<b>NFC/RFID Reader</b>	HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1
<b>GPS</b>	Yes
<b>Mobile Broadband</b>	4G LTE/AWS

## Accessories

- Digital Pen
- Desktop Charging Cradle



- 4-Bay System Gang Charger
- Battery Pack

