



704M/707M **Medical Grade Monitor**

Capacitive Touchscreen for Point-of-Care Applications

The DT Research 704M/707M Medical Grade Monitor is a slim, mountable and antimicrobial 24"/27" touchscreen, facilitating the system integration for healthcare applications. With Wi-Fi antennas and optional front camera (707M), this Medical Grade Monitor can be paired with personal computers, micro PCs, or thin clients for health professionals to manage information.






Features

- · High contrast 24" or 27" touchscreen
- Full-HD (1920 x 1080) resolution
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- Built-in speakers
- VESA compatibility for easy installation

Major Option

5 MP Front Camera (707M)

- B Speakers
- **C** DC-input
- D USB Type-B input
- HDMI
- **G** USB Type-B for touchscreen connection



Specifications





Model	704M	707M
System		
Display	23.8" touchscreen	27" touchscreen
Display Resolution	1920 x 1080	1920 x 1080
Viewing Angle	horizontal 89 degree, vertical 89 degree	horizontal 89 degree, vertical 89 degree
Number of Color	16.7M	16.7M
Brightness	250 cd/m2	300 cd/m2
Response Time	16 ms	7 ms
Control Button	1 screen on/off button, 1 menu button, 1 auto/exit button and 2 up/down buttons	1 screen on/off button, 1 menu button, 1 auto/exit button and 2 up/down buttons
Speaker and Microphone	Built-In Microphones and Speakers	Built-In Microphones and Speakers
I/O Ports		
USB Port	6 x USB 3.0	USB 3.0 x 6
USB Port for Touchscreen Connection	1 x USB Type-B (2.0)	USB Type-B (2.0) x 1
USB Input Port	1 x USB Type-B (3.0)	1 x USB Type-B (3.0)
HDMI	1	1
DC-in	1	1
Mechanical and Enviror	nmental	
Fan/Fanless	Fanless	Fanless
AC/DC Adapter	Input: 100 to 240V AC; Output: 19V DC, 3.78A	Input: 100 to 240V AC; Output: 19V DC, 3.78A
Enclosure	ABS + PC plastics, anti-microbial enclosure	ABS + PC plastics, anti-microbial enclosure
Dimensions (H x W x D)	14.6 x 22.3 x 1.8 in/ 370.5 x 567 x 45.2 mm	16.2 x 25.2 x 1.8 in/ 411.8 x 639.1 x 45 mm
Weight	16.14 lbs/ 7.32 kg	16.18 lbs/ 7.34 kg
VESA-compliant Mounting	100mm × 100mm VESA standard	100mm × 100mm VESA standard
Regulatory	ANSI/AAMI ES60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, IEC 62368-1, RCM, CCC	
Temperature	Operation: 0°C to 40°C (32°F to 104°F); Storage: -10°C to 50°C (14°F to 122°F)	
Humidity	0% to 90% non-condensing	
Major Options		

^{*} Specifications subject to change without notice.

Accessory



Camera



· Medical Grade Adapter







N/A

5 MP Front Camera