



DT302PA Rugged Tablet

Slim, Rugged, Multi-functional Wireless Computing

The DT302PA Rugged Tablet features the integration of a sunlight readable 10.1" capacitive touchscreen and a highperformance, energy-efficient Intel[®] Core[™] Ultra processor within a slim, lightweight, durable casing. With a built-in Wi-Fi module as well as options for front/ back cameras, barcode scanner, smart card reader, RFID and GNSS data capture modules, these robust tablets offer seamless information capture and transmission for improved workflow. IP65 rated, MIL-STD-810H and MIL-STD-461G certified with a wide temperature range, the DT302PA Rugged Tablet provides reliable operation in harsh, mission-critical environments.





Features

- 10.1" LED-backlit, sunlight-readable (1000 nits) touchscreen LCD, digital pen support
- Intel[®] Core[™] Ultra 5/7 processor
- Microsoft[®] Windows[®] 11 IoT Enterprise operating system
- NIST compliant BIOS available
- Hot-swappable battery for 24/7 operation
- Built-in microphone and speaker
- Detachable keyboard option for 2-in-1 applications
- IP65 rated, MIL-STD-810H and MIL-STD-461G certified
- Quick Access SSD
- Energy Star 8.0 certified

Major Options

- 5 MP Front Camera and 13 MP Back Camera
- 2D Barcode Scanner (Reads 1D and 2D)
- 4G LTE
- GPS Module
- * 4G Module cannot build on same device with 2D Scanner and GPS Module.

Specifications



DT302PA

|--|

System	
CPU	Intel® Core™ Ultra 5 Processor 225U, 12 core (up to 4.80 GHz) Intel® Core™ Ultra 7 Processor 255U, 12 core (up to 5.20 GHz)
RAM	16G to 32G LPDDR5
Storage	256GB to 4TB *Support quick access SSD function to easily replace the SSD without opening the back cover.
Operating System	Microsoft [®] Windows [®] 11 IoT Enterprise
NIST Compliance	NIST Compliant BIOS Available
Display	10.1" LED-Backlit, Sunlight-Readable (1000 nits) Touchscreen LCD
Display Resolution	1920 x 1200
Switch and Buttons	1 X Power Button, 2 X Brightness Control Buttons, 5 X Programmable Buttons
Microphone	Built-In Microphone
Speaker	Built-In 2W Speaker

Network Interface

WLAN	Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band
вт	5.3

I/O Ports

USB Ports	1 x USB3.2 (Type-A), 1 x USB3.2 latest USB/charging	
Headset Jack	1 (3.5 mm)	Standard
Ethernet Port	1 x Ethernet 10/100/1000MB Base-T LAN	Standard
DC-In Jack	1	
24-pin Fischer Minimax Connector	1 x USB2.0, COM port, RJ45, Power 5A (in), and Power 2A (out)	Optional

Mechanical and Environmental

AC/DC Adapter	Input: 100 to 240V AC; Output: 19V DC, 3.42A (65W)
Battery Pack	Hot-Swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-Swappable Battery (11.4V, 5400mAh) (Optional) 90W Hot-Swappable Battery, (11.4V, 8000mAh)
Enclosure	ABS + PC plastics and magnesium-aluminum alloy with anti-microbial coating
Dimensions (H x W x D)	7.7 x 10.71 x 0.79 in/195.6 x 272 x 20 mm
Weight	3 lbs/1.32 kg
Durability	IP65, MIL-STD-810H and MIL-STD-461G Certified
Regulatory	CE, FCC Class B, IC, CB, RCM, IEC 60601-1, IEC62680, EPEAT, Energy star 8.
Temperature	Operation*: -10°C to 60°C (14°F to 140°F) Storage: -50°C to 70°C (-58°F to 158°F)
Humidity	0% to 90% Non-Condensing
Major Options	
Barcode Scanner	2D Barcode Scanner (Reads 1D and 2D)

Barcode Scanner	2D Barcode Scanner (Reads 1D and 2D)
Camera	5 MP Front Camera and 13 MP Back Camera
GNSS	GPS
Mobile Broadband	4G LTE

* Specifications subject to change without notice.



Accessories

Digital Pen	
Pen Tip	Diameter: 0.059 in/1.5mm, replaceable
Buttons	2 side buttons (right-click and eraser)
Battery	1 AAAA, replaceable
Color	Black
Dimensions	Length: 5.5 in/140 mm (including pen tip) Diameter: 0.38 in/9.7 mm
Weight	0.055 lbs/25 g

Slim Detachable Keyboard

Designed to connect to DT302RP tablet without switching and pairing.



Tablet Mount Cradle

Offers Tablet storage and security with power supply and I/O ports.



VESA Mounting Bracket

Offers Tablet storage and security.

Battery Charging Kits



Battery Pack



