



DT361DF Tactical Tablet

Slim, Rugged, Multi-functional Wireless Computing

The DT361DF Tactical Tablet features a 6" LED 850 nits touchscreen with a high-performance, energy-efficient Intel® Core™ i3-N305 processor within a slim, lightweight, durable package. With built-in Wi-Fi, BT connectivity, optional night vision screens, GPS and front/back cameras options, the robust tablet offers seamless information capture and transmission for improved workflow. The DT361DF Tactical Tablet provides reliable operation in harsh, mission-critical environments.

Features



- 6" LED 850 nits touchscreen, capacitive stylus support
- Intel® Core™ i3-N305 processor
- Microsoft® Windows® 11 operating system
- IP65-rated for water and dust resistance
- Swappable battery pack



Major Options

- Night vision screen
- 5 MP front camera and 13 MP back camera
- Wide operating temperature range
- GPS module
- Waterproof 24-pin Fischer MiniMax connector

Specifications




Model	DT361DF	
System		
CPU	Intel® Core™ i3-N305, Octa-core (up to 3.8 GHz)	
Storage and RAM	512GB or 1TB removable SSD with 16GB RAM	
Operating System	Microsoft® Windows® 11 IoT Enterprise	
NIST Compliance	NIST compliant BIOS available	
Display	6" LED 850 nits touchscreen Default: 1080 x 2160 Optional NVIS panel: 1440 x 720	
Buttons	1 x power button, 1 x NVIS/daylight button, 2 x programmable buttons	
Microphone	Built-in microphone	
Speaker	Built-in speaker	
Network Interface		
WLAN	Wi-Fi 802.11ax, 2.4/5/6 GHz three band	
BT	5.3	
I/O Ports		
USB Port	1 x latest USB/charging; 1 x USB-A	
Ethernet	Ethernet 10/ 100/ 1000MB Base-T LAN	
DC-in Jack	1	
24-pin Fischer Minimax Connector (optional) * Eliminates the USB, Ethernet, and DC-in ports on the bottom.	Ethernet, USB-3.2 5G/USB2.0, and power 5-6A (in) and power 2A (out)/ground/URAT	
microSD Slot (optional)	1 x microSD card slot	
Mechanical and Environmental		
AC/DC Adapter	Input: 100 to 240V AC; Output: 12V DC, 5A	
Battery Pack	23W swappable battery (7.6V, 3100mAh)	
Enclosure	ABS + PC plastic and magnesium-aluminum alloy	
Dimensions (H x W x D)	3.73 x 7.7 x 1.4 in / 94.8 x 196 x 35.78 mm (with strap)	
Weight	1.23 lb/ 560 g (with battery)	
Regulatory	FCC Class B, CE, RoHS compliant Operation*: 0°C to 50°C (32°F to 122°F) Optional: -30°C to 60°C (-22°F to 140°F) Storage: -50°C to 70°C (-58°F to 158°F)	
Temperature		
Humidity	0% to 90% non-condensing	
Major Options		
Night Vision Screen	Luminance Option 1: Daylight mode: 800 nits; NVIS mode: 0 to 20 nits. MIL-STD-3009 Class B compliant, providing clear readability of display with the naked eye in dark environments, does not interfere with NVGs. Option 2: Daylight mode: 800 nits; NVIS mode: 0 to 0.7 nits. MIL-STD-3009 Class B compliant, providing clear readability of display with NVGs in dark environments.	
Camera	5 MP front camera and 13 MP back camera	
GNSS Module	GPS module	

* Specifications subject to change without notice.

Accessories

- Capacitive Stylus
- 6-Bay Battery Gang Charger
- Battery Pack
- Vest Tablet Mount



Product Configurator

