



DT362WF Handheld Rugged Tablet

Slim, Rugged, Multi-Functional Wireless Computing

The DT362WF Handheld Rugged Tablet features the Microsoft® Windows® operating systems enabling flexible integration with many applications. With a powerful Intel® Core™ i3-N305 processor, the handheld tablet offers high-performance and energy-efficient operations, while the slim and robust design enhances portability and mobility. With built-in Wi-Fi, BT connectivity, along with optional features such as 2D barcode scanner, 5 MP front camera and 13 MP back camera, and GPS to enhance versatility, the DT362WF Handheld Rugged Tablet guarantees reliable operation and expansive functionality for demanding, mission-critical environments.



Features

- 6" touchscreen, digital pen support
- Intel® Core™ i3-N305 processor
- Microsoft® Windows® 11 IoT Enterprise or operating system
- Hot-swappable battery pack
- IP65-rated for water and dust resistance
- Built in smart card/CAC reader

Major Options

- Barcode scanner or long range barcode scanner
- 5 MP front camera and 13 MP back cameras
- GPS module

Specifications



Model	DT362WF
System	
CPU	Intel® Core™ i3-N305, Octa-core (up to 3.8 GHz)
RAM	16GB
Storage	512GB to 1TB
Operating System	Microsoft® Windows® 11 IoT Enterprise
NIST Compliance	NIST compliant BIOS available
Display	6" LED-Backlit 850 nits touchscreen
Display Resolution	2160 x 1080 (2K)
Smart Card/CAC Reader	Full-slot (reads ISO 7816 T=0, T=1); 1.8/3/5V smart card
Buttons	1 x power button, 2 x programmable buttons
Speaker	Built-in speaker
Microphone	Built-in microphone
Network Interface	
WLAN	Wi-Fi 802.11ax, 2.4/5/6 GHz three band
BT	5.3
I/O Ports	
USB Ports	USB Type-C x 1 (data transmitting and charging; data transmitting only available in one insertion direction)
microSD Slot	1 x microSD Slot
Mechanical and Environmental	
AC/DC Adapter	Input: 100 to 240V AC; Output: latest USB/charging (65W, up to 20V/3.25A)
Battery Pack	Hot-swappable battery (2700mAh)
Enclosure	ABS + PC plastic
Dimensions (H x W x D)	7.6 x 3.7 x 1.2 in/192 x 95 x 31 mm
Weight	1.1 lbs/485 g
Regulatory	CE, FCC Class B, RoHS, UL
Temperature	Operation: 0°C to 50°C (32°F to 122°F); Storage: -50°C to 70°C (-58°F to 158°F)
Humidity	0% to 90% non-condensing
Major Option	
Camera	5 MP front USB camera and 13 MP back USB camera
Barcode Scanner	2D barcode scanner (Reads 1D and 2D) Long range 2D barcode scanner (up to 60ft)
GNSS Module	GPS module

* Specifications subject to change without notice.

Accessories

- Digital Pen
- 6-Bay Battery Gang Charger
- Battery Pack

