



# **LT355 Rugged Mobile Workstation**

## **Purpose-Built for Mission-Critical Environments**

The LT355 Rugged Mobile Workstation features the integration of a 15.6" touchscreen, an Intel<sup>®</sup> Core<sup>™</sup> i7/i5 processor, and a full-sized keyboard set. With the built-in Wi-Fi, BT, and smart card/CAC reader, the LT355 offers seamless information capture for instant transmission and is ideal for use either in the field or in the office. While its large, high-brightness (1200 nits) LCD touchscreen provides a clear view to enhance the degree of visual comfort, the optional embedded NVIDIA RTX<sup>™</sup> graphics card guarantees even higher performance and efficiency by enabling the LT355 to process demanding tasks such as rendering, image analysis, and artificial intelligence (AI). With an IP65 rating, the LT355 is ideal for operations in demanding, mission-critical environments.





#### **Features**

- 15.6" high-brightness (1200 nits) touchscreen, digital pen support
- Intel<sup>®</sup> Core<sup>™</sup> i7/i5 processor
- Microsoft<sup>®</sup> Windows<sup>®</sup> 10/11 IoT Enterprise operating system
- NIST compliant BIOS available
- Back-lit keyboard with multi-touchpad
- Built-in Wi-Fi and BT
- Built-in smart card/CAC reader
- SSD slot to support RAID 0/RAID 1
- Dual RAM slots, up to 64GB
- Dual hot-swappable batteries for 24/7 operation
- IP65-rated for water and dust resistance
- Energy Star 8.0 certified

### **Major Options**

- Embedded NVIDIA RTX™ A1000 or A2000 MXM graphics card
- Night vision screen

# Specifications



System	
CPU	Intel® Core™ i5-1340P, 12-Core, up to 4.6 GHz Intel® Core™ i7-1370P, 14-Core, up to 5.2 GHz
RAM	8GB to 64GB (Dual-Slot)
Storage	64GB to 2TB SSD (Supports Removable SSD and RAID)
Operating System	Microsoft <sup>®</sup> Windows <sup>®</sup> 10/11 IoT Enterprise
NIST Compliance	NIST compliant BIOS available
Display	15.6" high-brightness (1200 nits) touchscreen
Display Resolution	1920 × 1080
Trusted Platform Module	fTPM 2.0
Microphone	Built-In microphone
Speaker	Built-In speaker
Keyboard	
Keys	QWERTY, full row of F1 to F12 function keys Keys for Windows shortcuts, media controls, screen brightness
Backlight	Yes
Touch Pad	Multi-touch
Wireless Network Interface	
WLAN	Wi-Fi 802.11ax 2.4/5/6 Ghz three band
вт	Yes
I/O Ports	
USB Port	3 x USB-A
Ethernet	1 (Ethernet 10/100/1000MB Base-T LAN)
COM Port	1
HDMI-out	1
Smart Card/CAC Reader	1
Buttons	1 x Power Button, 4 x Programmable Touch Buttons
Mechanical and Environmental	
AC/DC Adapter	Input: 100 to 240V AC; Output: 19V, 230W Adapter
Battery Pack	(Optional) 2 x 60W/90W Hot-Swappable Batteries (11.4V, 5400mAh)
Enclosure	ABS + PC Plastic and Magnesium-Aluminum Alloy
Dimensions (H x W x D)	1.66 x 15.16 x 10.57 in/42.05 x 385 x 268.5 mm
Weight	9.70 lbs/4.4 kg
Durability	IP65
Certifications	FCC Class B, CE, RoHS, Energy Star 8.0, RCM Compliant
Temperature	Operation: -10°C to 60°C (14°F to 140°F), Optional: -30°C to 60°C (-22°F to 140°F) Storage: -55°C to 70°C (-67°F to 158°F)
Humidity	0% to 90% Non-Condensing
Major Option	
Graphics Card	Embedded MXM GPU Module with Embedded NVIDIA RTX™ A1000 or A2000 MXM
Night Vision Screen Luminance	Option 1: Daylight mode: 800 nits; NVIS mode: 0 to 20 nits. MIL-STD-3009 Class B compliant, providing clear readability of display with the naked eye in dark environments, does not interfere with NVGs. Option 2: Daylight mode: 800 nits; NVIS mode: 0 to 0.7 nits. MIL-STD-3009 Class B compliant, providing clear readability of display with NVGs in dark environments.

\* Specifications subject to change without notice.













DT Research, Inc. 2000 Concourse Drive, San Jose, CA 95131 
 NCSCCIICII
 2000 Concourse Drive, San Jose, CA 95131

 www.dtresearch.com
 Copyright © 2023, DT Research, Inc. All Rights Reserved.

www.dtresearch.com/productconfig